

臺灣瑞昶電機股份有限公司
东莞市瑞昶电机有限公司

服務熱線: 400-66-222-80
HTTP://www.rcdj.com.cn
E-mail:hb@rcdj.com.cn

CRELEC鼓風機選型表 (性能參數)

HB系列 HB-Series
三相電機 雙段式 IP55 2P

型號 Model (SAC)	單級 雙級	頻率 frequency	功率 power	馬達參數		最大 排吸流量 Max air flow	額定 真空壓力 rated Vacuum	額定 壓縮壓力 rated compress	噪音 noises	重量 Weight	口徑 Price
				額定電壓	額定電流						
				voltage	current						
HB-139	單	50	0.25	200-240Δ/345-415Y	2.1Δ/1.2Y	70	-110	120	48	7	G1.2"
		60	0.29	220-275Δ/380-480Y	2.0Δ/1.15Y	85	-140	150	50		
HB-229	單	50	0.4	200-240Δ/345-415Y	2.6Δ/1.5Y	80	-120	130	53	10	G1.2"
		60	0.5	220-275Δ/380-480Y	2.6Δ/1.5Y	96	-150	160	56		
HB-229L	單	50	0.4	200-240Δ/345-415Y	2.6Δ/1.5Y	105	-120	130	54	11	G1.2"
		60	0.5	220-275Δ/380-480Y	2.6Δ/1.5Y	120	-150	160	57		
HB-239	單	50	0.55	200-240Δ/345-415Y	2.8Δ/1.6Y	100	-110	120	55	11	G1.2"
		60	0.63	220-275Δ/380-480Y	3.0Δ/1.7Y	120	-110	120	57		
HB-239L	單	50	0.55	200-240Δ/345-415Y	2.8Δ/1.6Y	140	-60	60	56	12	G1.2"
		60	0.63	220-275Δ/380-480Y	3.0Δ/1.7Y	165	-50	50	58		
HB-249	單	50	0.75	200-240Δ/345-415Y	3.8Δ/2.2Y	100	-150	150	55	12	G1.2"
		60	0.85	220-275Δ/380-480Y	3.8Δ/2.2Y	120	-150	140	57		
HB-249L	單	50	0.75	200-240Δ/345-415Y	3.8Δ/2.2Y	140	-100	100	56	13	G1.2"
		60	0.85	220-275Δ/380-480Y	3.8Δ/2.2Y	165	-115	100	58		
HB-329	單	50	0.75	200-240Δ/345-415Y	3.8Δ/2.2Y	145	-120	120	63	15	G1.5"
		60	0.85	220-275Δ/380-480Y	3.8Δ/2.2Y	175	-140	140	64		
HB-329L	單	50	0.75	200-240Δ/345-415Y	3.8Δ/2.2Y	180	-70	70	64	14	G1.5"
		60	0.85	220-275Δ/380-480Y	3.8Δ/2.2Y	210	-50	50	65		
HB-329-1	單	50	0.9	200-240Δ/345-415Y	4.0Δ/2.3Y	145	-160	160	63	17	G1.5"
		60	1.1	220-275Δ/380-480Y	3.85Δ/2.25Y	175	-160	160	64		
HB-329L-1	單	50	0.9	200-240Δ/345-415Y	4.2Δ/2.4Y	180	-110	100	64	17	G1.5"
		60	1.1	220-275Δ/380-480Y	4.0Δ/2.3Y	210	-90	70	65		
HB-339	單	50	1.3	200-240Δ/345-415Y	5.7Δ/3.3Y	145	-170	200	63	18	G1.5"
		60	1.5	220-275Δ/380-480Y	6.0Δ/3.5Y	175	-210	220	64		
HB-339L	單	50	1.3	200-240Δ/345-415Y	6.6Δ/3.8Y	180	-180	180	64	18	G1.5"
		60	1.5	220-275Δ/380-480Y	6.9Δ/4.0Y	210	-210	170	65		
HB-429-1	單	50	0.9	200-240Δ/345-415Y	4.0Δ/2.3Y	210	-110	100	64	20	G2"
		60	1.1	220-275Δ/380-480Y	4.2Δ/2.3Y	255	-80	70	70		
HB-429L-1	單	50	0.9	200-240Δ/345-415Y	4.2Δ/2.3Y	270	-40	40	65	21	G2"
		60	1.1	220-275Δ/380-480Y	4.0Δ/2.3Y	330	-40	40	70		
HB-429-2	單	50	1.5	200-240Δ/345-415Y	6.6Δ/3.8Y	210	-170	170	64	22	G2"
		60	1.75	220-275Δ/380-480Y	6.9Δ/4.0Y	255	-150	140	70		
HB-429L-2	單	50	1.5	200-240Δ/345-415Y	6.6Δ/3.8Y	270	-120	110	65	23	G2"
		60	1.75	220-275Δ/380-480Y	6.9Δ/4.0Y	330	-90	80	70		
HB-429	單	50	1.75	200-240Δ/345-415Y	7.5Δ/4.3Y	210	-200	190	64	23	G2"
		60	1.9	220-275Δ/380-480Y	7.6Δ/4.4Y	255	-220	220	70		
HB-429L	單	50	1.75	200-240Δ/345-415Y	7.5Δ/4.3Y	270	-160	150	65	24	G2"
		60	1.9	220-275Δ/380-480Y	7.6Δ/4.4Y	330	-160	150	70		
HB-439	單	50	2.2	200-240Δ/345-415Y	9.7Δ/5.6Y	210	-220	270	64	26	G2"
		60	2.55	220-275Δ/380-480Y	10.3Δ/6.0Y	255	-260	290	70		
HB-439L	單	50	2.2	200-240Δ/345-415Y	9.7Δ/5.6Y	270	-220	230	65	26	G2"
		60	2.55	220-275Δ/380-480Y	10.3Δ/6.0Y	330	-260	260	71		
HB-519	單	50	1.75	200-240Δ/345-415Y	8.5Δ/4.9Y	265	-180	190	67	24	G2"
		60	1.9	220-275Δ/380-480Y	8.8Δ/5.5Y	315	-180	190	70		
HB-519L	單	50	1.75	200-240Δ/345-415Y	8.5Δ/4.9Y	345	-125	125	70	26	G2"
		60	1.9	220-275Δ/380-480Y	8.8Δ/5.5Y	415	-105	130	73		
HB-529	單	50	2.2	200-240Δ/345-415Y	9.7Δ/5.6Y	265	-235	220	67	27	G2"
		60	2.55	220-275Δ/380-480Y	10.3Δ/6.0Y	315	-245	230	70		
HB-529L	單	50	2.2	200-240Δ/345-415Y	9.7Δ/5.6Y	345	-205	195	70	29	G2"
		60	2.55	220-275Δ/380-480Y	10.3Δ/6.0Y	415	-170	195	73		
HB-539	單	50	3	200-240Δ/345-415Y	12.5Δ/7.2Y	270	-280	280	69	32	G2"
		60	3.45	220-275Δ/380-480Y	12.6Δ/7.3Y	315	-260	270	78		
HB-539L	單	50	3	200-240Δ/345-415Y	12.5Δ/7.2Y	345	-240	220	70	35	G2"
		60	3.45	220-275Δ/380-480Y	12.6Δ/7.3Y	415	-210	220	73		
HB-629	單	50	3.4	200-240Δ/345-415Y	12.5Δ/7.2Y	318	-270	290	69	36	G2"
		60	3.7	220-275Δ/380-480Y	12.6Δ/7.3Y	376	-240	230	72		
HB-629L	單	50	3.4	200-240Δ/345-415Y	12.5Δ/7.2Y	420	-220	200	70	37	G2"
		60	3.7	220-275Δ/380-480Y	12.6Δ/7.3Y	500	-200	170	73		




臺灣瑞昶電機股份有限公司
东莞市瑞昶电机有限公司

服務熱線: 400-66-222-80
HTTP://www.rcdj.com.cn
E-mail:hb@rcdj.com.cn

CRELEC鼓風機選型表 (性能參數)

HB系列 HB-Series
三相電機 雙段式 IP55 2P

型號 Model (SAC)	單級 雙級	頻率 frequency	功率 power	馬達參數		最大 排吸流量 Max air flow	額定 真空壓力 rated Vacuum	額定 壓縮壓力 rated compress	噪音 noises	重量 Weight	口徑 Price
				額定電壓	額定電流						
				voltage	current						
HB-639	單	50	4	345-415Δ/600-720Y	9.0Δ/5.2Y	318	-290	360	69	40	G2"
		60	4.6	380-480Δ/660-720Y	9.0Δ/5.2Y	376	-320	310	72		
HB-639L	單	50	4	345-415Δ/600-720Y	9.0Δ/5.2Y	420	-260	280	70	43	G2"
		60	4.6	380-480Δ/660-720Y	9.0Δ/5.2Y	500	-260	260	73		
HB-729	單	50	5.5	345-415Δ/600-720Y	12.9Δ/7.4Y	530	-300	320	80	62	G2.5"
		60	6.3	380-480Δ/660-720Y	12.9Δ/7.4Y	620	-320	340	82		
HB-729L	單	50	5.5	345-415Δ/600-720Y	12.9Δ/7.4Y	700	-200	180	70	66	G2.5"
		60	6.3	380-480Δ/660-720Y	12.9Δ/7.4Y	840	-180	180	74		
HB-829	單	50	7.5	345-415Δ/600-720Y	16.7Δ/9.6Y	530	-320	380	80	65	G2.5"
		60	8.6	380-480Δ/660-720Y	17.3Δ/10Y	620	-350	400	82		
HB-829L	單	50	7.5	345-415Δ/600-720Y	16.7Δ/9.6Y	700	-270	260	70	69	G2.5"
		60	8.6	380-480Δ/660-720Y	17.3Δ/10Y	840	-270	260	74		
HB-919	單	50	9	345-415Δ/600-720Y	18.2Δ/10.5Y	1050	-190	190	74	93	G4"
		60	11	380-480Δ/660-720Y	18.2Δ/10.5Y	1250	-150	140	79		
HB-919L	單	50	9	345-415Δ/600-720Y	18.2Δ/10.5Y	1370	-120	110	75	98	G4"
		60	11	380-480Δ/660-720Y	18.2Δ/10.5Y	1650	-80	70	80		
HB-929	單	50	13	345-415Δ/600-720Y	28Δ/16.2Y	1050	-290	280	74	116	G4"
		60	15	380-480Δ/660-720Y	29Δ/16.7Y	1250	-270	260	79		
HB-929L	單	50	13	345-415Δ/600-720Y	28Δ/16.2Y	1370	-190	180	75	121	G4"
		60	15	380-480Δ/660-720Y	29Δ/16.7Y	1650	-150	150	80		
HB-929-1	單	50	15	345-415Δ/600-720Y	35Δ/20Y	1050	-320	380	74	120	G4"
		60	17.5	380-480Δ/660-720Y	36.5Δ/21Y	1250	-250	250	75		
HB-929L-1	單	50	15	345-415Δ/600-720Y	35Δ/20Y	1370	-250	250	75	129	G4"
		60	17.5	380-480Δ/660-720Y	36.5Δ/21Y	1650	-200	200	80		
HB-939	單	50	20	345-415Δ/600-720Y	37Δ/21Y	1050	-360	460	74	126	G4"
		60	23	380-480Δ/660-720Y	39Δ/22.5Y	1250	-380	420	79		
HB-939L	單	50	20	345-415Δ/600-720Y	37Δ/21Y	1370	-310	320	75	131	G4"
		60	23	380-480Δ/660-720Y	39Δ/22.5Y	1650	-300	280	80		



臺灣瑞昶電機股份有限公司
东莞市瑞昶电机有限公司

服務熱線: 400-66-222-80
HTTP://www.rcdj.com.cn
E-mail:hb@rcdj.com.cn

CRELEC鼓風機選型表 (性能參數)

HB系列 HB-Series
三相電機 雙段式 IP55 2P

型號 Model (SAC)	單級 雙級	頻率 frequency	功率 power	馬達參數		最大 排吸流量 Max air flow	額定 真空壓力 rated Vacuum	額定 壓縮壓力 rated compress	噪音 noises	重量 Weight	口徑 Price
				額定電壓	額定電流						
				voltage	current						
HB-2308	雙	50	0.75								